ENGLISH - STREAM CROSSING STRUCTURE SURVEY REPORT Wisconsin Department of Transportation DT1698 1/2002 (Replaces EB53) Box Culvert ☐ Culvert Extension Right □ Stream Crossing ☐ Other Left Preliminary Plan Due Date Final Plan Due Date Town of (N/A for Culverts) Village of City of New Structure Number Highway County Design Project ID Construction Project ID Aesthetics Level (For Levels 2, 3 & 4, Explain on Page 4) ___2 3 4 1 Station Section Town Range Indicate Purpose Identify Stream (If Applicable) Waterway Other (Describe) District Contact Person/Area Code with Telephone Number Traffic Forecast Data

Instructions for Structure Survey

Design Year

Average

Traffic (ADT)

Daily

Roadway

Design

Speed

mph

Functional

Class

In addition to this report, the following information shall be submitted.

- 1. **Small County Map** on which the location of proposed structure is shown in red and highway relocation, if any, in green.
- 2. **Plan and Profile Sheet** on proposed reference line of highway showing the following: (a) Ground line; (b) Finished grade line; (c) Profile grade line elevations at least every 100 feet for 1,000 feet each side of the structure; (d) Vertical curve control points; (e) Horizontal curve control points; (f) Curve data, including full SE and runoff distance.
- 3. **Contour Map** of the site drawn to a scale of not less than 1" = 20 feet with one-foot contours and showing the following (a) Existing highway and structure; (b) Proposed highway alignment and R/W; (c) Station numbers; (d) North point; (e) Buildings; (f) Underground facilities; (g) Other features which influence the design; (h) Recommended channel change; (i) Direction of stream flow; (j) Stations at end of existing structure; (k) Proposed structure and extent of riprap for consultant designed structures.
- 4. **Typical Roadway Cross Section** of proposed approaches showing the following: (a) Dimensions; (b) Slopes; (c) Type and width of surfacing or pavement; (d) Sidewalk, curb and gutter; (e) Subgrade and pavement thickness; (f) Clear zone width.
- 5. **Stream Cross Section** at upstream and downstream face of existing bridge and at one bridge length upstream and downstream. Surface water elevations at 1500 feet upstream and downstream of existing bridge.
- 6. **Original Photographs** of: (a) Existing structure; (b) Upstream and downstream structures; (c) Buildings within 100 feet of the proposed structure; (d) Unobstructed panoramic view looking upstream and downstream from proposed structure. *Air photo mosaics if available.*
- 7. **Proposed Location Map** showing structure location and number, one per structure when there are multiple structures on the project.
- 8. Attach a copy of the regulatory flood plain map (FEMA map) depicting the site.

Consultant Contact Person/Area Code with Telephone Number

9. For consultant designed structures - Hydraulic Report which may contain the following: (a) USGS quadrangle sheet showing proposed location, highway alignment and reach of river; (b) All available flood history, high water marks with date of occurrence, nature of flooding, damages and scour information; (c) Factors affecting water stages; (d) Navigation Clearance, for guidance in making report, see Chapter 8 of Bridge Design Manual; (e) Discussion of alternatives considered, factors influencing selection.

Proposed Structure

	Structure Type at	thia Cita		Chack has	e if to be deterr	mined by Cent	ral Office	
Freierence ior .	Structure Type at	i iiis site		☐ Check her	e ii to be deteri	illiled by Cerit	rai Office	
Roadway Width Between Curbs Ft.			Cross Slope on Deck or N.C. (Normal Crown) Ft./Ft.					
Sidewalks - Number Sidewalk Clear Width								
Charify Wing Location for Doors Cyand Attachment			Ft.					
Specify Wing Location for Beam Guard Attachment			Specify Clear Zone Width when Beam Guard not Used on Culvert					
Specify Wing Location for Surface Drain Anchors			Specify Wing Location where Bridge Barrier/Rail Continues on Roadway Approach					
YES NO				YES NO				_
☐ ☐ Is Project in Flood Hazard Area			Structure Backfill Required					
☐ Have Soil Borings been Requested			Riprap Required					
	(If not, Plea Staged Cor		n on Page 4)	Lighting Required on Bridge				
H H	Temporary		Required	Bolt Circle Diameter mm Camber for Barrel Recommended				
	, ,		•	(Culvert only)				
Duamarad D		f	04		Is this proje	ect on the Nati	onal Highway Syst	em?
Proposed D	isposition of	Existing	Structure					
YES NO								
	•		e Removed	, 5, 0				
- H - F			included in Struemain in Service		iantities re Number			
☐ Special	•		Required - See			Report"		
			ture, complete			· · · · · · · · · · · · · · · · · · ·		
Type	Size	1 110 011 00	•	ze at Abutmer		Weight	Pressure	
-			For Str	ucture Desi	aners Use	_		
				posed Box (
Aprons Type					Elevations			
Inlet								
Inlet								
Outlet								
	nber		Clear Span at Rig	iht Angles to Axis	of Box	Inside Height o	f Box	
Outlet			Clear Span at Rig	ht Angles to Axis	of Box	Inside Height o	f Box	
Outlet Openings - Nur			Clear Span at Rig	iht Angles to Axis	of Box	Inside Height o	f Box	
Outlet Openings - Nur Slope of Chann	el at Culvert		All P	roposed Str	uctures		f Box	
Outlet Openings - Nur	el at Culvert			roposed Str	uctures	Skew	f Box R.H.F. □ L.H.F.	
Outlet Openings - Nur Slope of Chann Spans - Number	el at Culvert	_ Sq. Mi.	All P	roposed Str	uctures structure)	Skew		
Outlet Openings - Nur Slope of Chann Spans - Numbe	el at Culvert	•	All P Spans Lengths (C	roposed Str	uctures structure)	Skew	R.H.F. 🗌 L.H.F.	
Outlet Openings - Nur Slope of Chann Spans - Number Drainage Area High Water (1	el at Culvert er a	Ft.	All P Spans Lengths (C Q (100) Q (Struct.)	roposed Str C.L. to C.L. of Sub	uctures structure) cfs cfs	Skew	R.H.F.	
Outlet Openings - Nur Slope of Chann Spans - Number Drainage Area High Water (1	el at Culvert er a	Ft.	All P Spans Lengths (C Q (100) Q (Struct.) Q (Rdwy.)	roposed Str	uctures structure) cfs cfs cfs	Skew	R.H.F. 🗌 L.H.F.	
Outlet Openings - Nur Slope of Chann Spans - Number Drainage Area High Water (1 Velocity Waterway Area	el at Culvert er a	Ft.	All P Spans Lengths (C Q (100) Q (Struct.)	roposed Str	uctures structure) cfs cfs cfs	Skew	R.H.F.	
Outlet Openings - Nur Slope of Chann Spans - Number Drainage Area High Water (1 Velocity Waterway Area Scour Code	el at Culvert er a 00) ea	Ft.	All P Spans Lengths (C Q (100) Q (Struct.) Q (Rdwy.) Q (Suple. Struct)	roposed Str C.L. to C.L. of Sub	uctures structure) cfs cfs cfs cfs cfs	Skew Existing Brid High Water (1	R.H.F.	
Outlet Openings - Nur Slope of Chann Spans - Number Drainage Area High Water (1 Velocity Waterway Area Scour Code Temporary S	el at Culvert er a 00) ea tructure	Ft. Ft/Sec. Sq. Ft.	All P Spans Lengths (C Q (100) Q (Struct.) Q (Rdwy.) Q (Suple. Struct.)	roposed Str C.L. to C.L. of Sub tt.)	uctures structure) cfs cfs cfs cfs cfs	Skew	R.H.F.	
Outlet Openings - Nur Slope of Chann Spans - Number Drainage Area High Water (1 Velocity Waterway Area Scour Code Temporary S Q Yr.	el at Culvert er a 00) ea	Ft. Ft/Sec. Sq. Ft.	All P Spans Lengths (C Q (100) Q (Struct.) Q (Rdwy.) Q (Suple. Struct) Overtopping F Q Yr.	roposed Str C.L. to C.L. of Sub	uctures structure) cfs cfs cfs cfs cfs	Skew Existing Brid High Water (1	R.H.F.	
Outlet Openings - Nur Slope of Chann Spans - Number Drainage Area High Water (1 Velocity Waterway Area Scour Code Temporary S	el at Culvert er a 00) ea tructure	Ft. Ft/Sec. Sq. Ft.	All P Spans Lengths (C Q (100) Q (Struct.) Q (Rdwy.) Q (Suple. Struct.)	t.)	uctures structure) cfs cfs cfs cfs cfs	Skew Existing Brid High Water (1	R.H.F.	

Existing Structures At or Near Proposed Site

	STRUCTURE DATA	UPSTREAM	AT SITE	DOWNSTREAM
Structure Number	er (B / P / C)			
Railroad or Highway Structure				
Distance from Proposed Site in Miles				
Type: S	Superstructure			
S	Substructure: Abutments			
	Piers			
Is Structure Supported on Bearing Piles?				
Condition: S	Superstructure			
5	Substructure			
Year Built				
Number of Spans	S			
Clear Span (Between Inside Faces of Substructure Units) Lengths Along CL Roadway/Track				
Roadway Width	Between Curbs			
	lumber			
	Clear Width			
L	ocation			
Skew: S	Stream			
5	Structure			
* Elevation	Finished Grade			
+ +	Low Chord			
Does Drift Pass	Satisfactorily			
Does Ice Pass Satisfactorily				
Character of Material in Stream Bed				
** Character of Drainage Basin				
Stream-Bed Scour: Visable (Y/N)				
Due to Restricted Waterway				
Due to Poor Location				
Due to Improper Skew				
Extreme High Water Elevation - Date				
Cause of High W	ater and Source of Information			
Low Water Eleva	ation			
Normal Water Elevation				
Streambed Elevation				
Water Surface	Date	1500' Upstream	At Site	1500' Downstream
Elevation ***				
•			•	•

Existing Culvert Information

Attach Sketc	ch			
Slope of Cha	annel at Structure (ft./100 ft.)			
Elevation:	Finished Grade	Spans:	Number	
	Inlet - Invert	Width Norma	ıl - Barrel	
- Top of Opening		Allowable High Water		
	Discharge - Invert	Floor: Concre	ete, Earth, Silted	
	- Top of Opening	Condition:	Wingwalls	
			Barrel	

- Use same datum for all structures within one-half mile of proposed structure.

 Mountains, Hilly, Rolling, Flat, Swampy, Wooded, Cultivated, Pasture, etc. Give percentage of each.

 Measured along thread of channel.
- Take these elevations at the same station.

Additional Information				
Elaborate on other concerns such as: DNR, Local, Aesthetics and Stage Construction				
FOR BRIDGE OFFICE USE				

Date

Plans Checked By